AE5511 TrafficTesterPro

AE5511

Specification

Item		Specification
Control port		10/100BASE-T(RJ-45) ×1
Console port		RS-232C(D-sub) ×1
LED display		POWER,STANDBY,HDD,REMOTE,STATUS,STATUS1,STATUS2,LINK
Power		AC90-264V,48-63Hz
Consumption electricity		200VA
Dimensions /Weight	Dimensions	Approx. 435 (W) × 88 (H) × 300 (D) mm Can be mounted on a 2U high 19 inch rack
	Weight	Approx. 7kg (AE5511 main unit only)
Unit packaging slot		2 slot
Operation Environment		Temperature range: 5°C-40°C Humidity range: 35°C-85°C
Standard accessories		User manual, start up manual, power cable, control port connection cable (1.5m long, cross over cable with RJ-45 connector), console port connection cable (1.5m long, RS-232C cross over cable), CD-ROM(AE5511 TTPro Control Window Application)

System Requirements

Item	Specification
PC	PC/AT Compatibility
OS	Windows2000 SP3, SP4, WindowsXP SP1, SP2
CPU	PentiumIII 1.2GHz or faster
Memory	more 512MB
HardDisk	Space capacity more than 200MB(Recommendation more 300MB)
Disk device	CD-ROM drive

Model/Specification Cords

■ AE5501 TrafficTesterMini

Product Name	Model Name	Code		Specification
AE5501 TrafficTesterMini	417322600			
		-A		Domestic standard
		-C		UL/CSA standard
		-E		VDE standard
		-G		SAA standard
		-S		BS standard
		-V		GB standard
			-LNJ	Japanese
			-LNE	English
AE5730E Setup Software	417322607			Note: Must order with main body

■ AE5511 TrafficTesterPro

Product Name	Model Name	Code		Specification
AE5511 TrafficTesterPro	417322900			
		-L		Domestic standard
		-C		UL/CSA standard
		-E		VDE standard
		-G		SAA standard
		-S		BS standard
		-V		GB standard
			-LNJ	Japanese
			-LNE	English
AE5520 10/100BASE-T Unit	417322901			
AE5521 1000BASE-X Unit	417322902			
AE5522 10GBASE-X Unit	417322904			
AE5523 1000BASE-T Unit	731010			
AE5524 1000BASE-X Unit	731011			

■ Trademarks Windows and Internet Explorer are registered trademarks or trademarks of Microsoft Corporation in the United States and other countries.
Pentium is a registered trademark or trademark of Intel Corporation

Notes) The contents of this document may be subject to change without prior notice with the improvements of the product performance and quality. There products may be under export control by the Japanese government as required by the Foreign Exchange and Foreign Trade Law.

YOKOGAWA

YOKOGAWA ELECTRIC CORPORATION
Communication & Measurement Business Headquarters /Phone: (81)-422-52-6768, Fax: (81)-422-52-6624
E-mail: tm@csv.yokogawa.co.jp
YOKOGAWA CORPORATION OF AMERICA Phone: (1)-301-916-0409, Fax: (1)-301-916-1498
YOKOGAWA EUROPE B.V. Phone: (31)-33-4641858, Fax: (31)-33-4641859
YOKOGAWA ENGINEERING ASIA PTE. LTD. Phone: (65)-62419933, Fax: (65)-62412606

Subject to change without notice.
[Ed : 02/b] Copyright ©2005
Printed in Japan, 508(KP)

MS-14E